

ELECA MICROPHONES

EM-10 Microphone

Impedance:
600Ω±30%
Frequency Response:
80-100kHz
Sensitivity (at 1kHz):
-70±3dB



LM-575 Microphone

Impedance:
600Ω±30%
Frequency Response:
80-130kHz
Sensitivity (at 1kHz):
-70±3dB



WM-6300 Dynamic Wireless Microphone

Miniature Receiver
100 ft. Operating Range



WM-6301 Dynamic Wireless Microphone

Miniature Receiver
Works as wired
or wireless
100 ft. Operating Range
Mic cable included



LWM-2020 Professional Quality Dual Microphone Wireless System

Audio Frequency Response: 40 - 15kHz
Dynamic Range: 100dB
System Distortion: 0.5%
Signal to noise Ratio: 100dB
Operating Range: 300ft
Carrier Frequency Range: 180 - 280 MHz



WM-6304

Dynamic Type
Uni-directional
Impedance: 600Ω±30%
Frequency Range: 100-130MHz
Frequency response: 80-12kHz
Sensitivity: -74 ± 3dB (1 kHz)
Voltage: 9V
Receiver Voltage: 110V AC
Eff. Distance: 100 ft.



WM-6310

Dynamic Type
Uni-directional
Impedance: 600Ω±30%
Frequency Range: 180-200MHz
Frequency response: 80-11kHz
Sensitivity: -72±3dB (1 kHz)
Voltage: 9V
Receiver Voltage: 110V AC
Eff. Distance: 100 ft.